

FILTERCLEAN

1. DESCRIPTION

- Based on a mixture of aliphatic and chlorinated aromatic hydrocarbons, cresols and anionic surface-active agents.
- Removes partially carbonized oils.
- Timely cleaning prevents the formation of coke-like adherents.
- Non-corrosive.

2. APPLICATIONS

FILTERCLEAN is mainly used for the cleaning of permanently fixed oil coolers, oil pre-heaters and metal-ceramic oil filters. These units are regularly contaminated by particles in the oil and partially carbonized oils. Timely cleaning prevents the formation of coke-like adherents, which are difficult or impossible to remove.

3. DIRECTIONS FOR USE

FILTERCLEAN is used undiluted at cleaning temperatures not exceeding 60°C. The cleaning effect is obtained by filling and/or circulating the product. Cleaning will take 8 to 24 hours depending upon the degree of contamination.

LIQUID CLEANING AGENT FOR REMOVAL OF PARTIALLY CARBONIZED OILS USING CIRCULATION METHOD

Product Highlights

- Removes partially carbonized oils.
- Timely cleaning prevents the formation of coke-like adherents.
- Non-corrosive.

Product Characteristics

Appearance:	Clear amber liquid
Corrosive action:	None
Specific gravity:	.90
Flash Point:	>80 C
pH:	7

This information is not to be taken as a warranty or representation for which we assume any legal responsibility. The information is offered solely for your consideration, investigation and verification

clean chemicals clean ships clean seas

