

MARISOL

1. DESCRIPTION

Alkaline cleaning agent containing alkaline salts and surfactants.

2. APPLICATIONS

Cleaning of soft and light non-oxidized vegetable and animal oil residues from tank surfaces.

Suitable for use on most tank coatings including aluminum, zinc alloy and other light metal alloys.

Cleaning of steam sides of condensers.

Cleaning of oil and grease residues in heat exchangers, preheaters etc.

3. DIRECTIONS FOR USE

High Pressure Work

- For high pressure work allow **MARISOL** to penetrate for about 3 to 5 minutes before washing off to prevent **MARISOL** from drying on the surface to be cleaned and forming edges: keep it damp. Cleaning effect is greatly increased by working with warm water.
- For HIGH PRESSURE work, dilute 1 liter of **MARISOL** with 5 liters of water.

Tank Cleaning

- Cleaning of tanks should, if possible, be carried out immediately after discharge of contents.

4. OTHER INFORMATION

- Light detergent power.
- Leave grease free surface.
- Rapid penetration.
- Rapid rinsing.
- Can be used on ferrous metals, aluminum, tin, zinc, copper and their alloys.
- Saves time and reduces labor costs.
- Non-corrosive.
- Non-caustic.
- Non-flammable.

MEDIUM DUTY ALKALINE CLEANER WATER BASED

(IMO APPROVED)

Product Highlights

- Light detergent power.
- Leave grease free surface.
- Rapid penetration.
- Rapid rinsing.
- Can be used on ferrous metals, aluminum, tin, zinc, copper and their alloys.
- Saves time and reduces labor costs.
- Non-corrosive.
- Non-caustic.
- Non-flammable.

Product Characteristics

Appearance:	Clear liquid
Corrosive action:	none
Specific gravity:	1.0(20°C)
Flash Point:	None
pH:	10

This information is not to be taken as a warranty or representation for which we assume any legal responsibility. The information is offered solely for your consideration, investigation and verification

clean chemicals clean ships clean seas

