

RUST OFF

1. DESCRIPTION

- Cleans and brightens aluminum and copper.
- Removes rust stains without risk to paint work.
- Safe on most common metals and bleaches wood.
- Removes time scale. Ideal for blanching tanks.

2. APPLICATIONS

UNI AMERICAS RUST OFF is used for the cleaning of aluminum floor plates, copper and brass fittings, wooden decks and removal of lime after tank cleaning operations.

3. DIRECTIONS FOR USE

In most cases **RUST OFF** is applied by brush diluted in solution ranging from 10-50% and left to react for 5-10 minutes. Smaller objects can be soaked in plastic container. After cleaning, rinse items thoroughly with a water jet.

Paintwork

Dilute **RUST OFF** 1 liter of product to 4-9 liters water (32 ounces to 1-3 gallons water), apply the solution by brush or spray using plastic equipment and leave to soak for 10-20 minutes. Rinse off using a powerful water jet with a brush, if necessary. Do not permit cleaning solution to come in contact with food in preparation or finished stage of processing.

Tank Cleaning

If lime scale stains are present after completion of tank cleaning operations, inject 0.5 liters (16 ounces), **RUST OFF** per 100 liters (25 gallons) wash water directly into the washing system for approximately 20 minutes. The recommended temperature is 75-85°C (165-185°F).

ACIDIC LIQUID PRODUCT FOR THE CLEANING OF ALUMINUM, COPPER AND REMOVAL OF RUST STAINS ON PAINT WORK

(IMO APPROVED)

Product Highlights

- Cleans and brightens aluminum and copper.
- Removes rust stains without risk to paint work.
- Safe on most common metals and bleaches wood.
- Removes time scale. Ideal for blanching tanks.

Product Characteristics

Appearance:	Clear liquid
Corrosive action:	Acid
Specific gravity:	1.2(20°C)
Flash Point:	None
pH:	<1

This information is not to be taken as a warranty or representation for which we assume any legal responsibility. The information is offered solely for your consideration, investigation and verification

clean chemicals clean ships clean seas

